TANG ABC DRY CHEMICAL EXTINGUISHER

CE
0029

KM 549399
EN3

Tang range come with BRASS valve, Song range come with ALUMI. Valve

- Typical Uses: For public areas such as offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas.
- For businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/ aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.
- Not recommended for use on sensitive electronic equipment or aircraft structure.

Technical Data

Model # Brass Valve Model #Alum Valve	Tang PD1E N/A	Tang PD1 N/A	Tang PD2 Song PD2	Tang PD3 Song PD3	Tang PD4 Song PD4	Tang PD6 Song PD6	Tang PD9 Song PD9	Tang PD12 Song PD12
Propellant Type	Store Pressure							
Extinguishing Medium	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder
Capacity(kg)	1	1.	2	3	4	6	9	12
Height(mm)	292	310	380	420	472	525	545	675
Shell Diameter(mm)	Φ85	Φ90	Φ110	Φ130	Φ130	Φ154	Φ182	Φ190
Cylinder Volume	1.13	1.23	2.30	3.75	4.60	6.78	10.31	15
Working Pressure(bar)	15	15	15	15	15	15	15	15
Test Pressure(bar)	27	27	27	27	27	27	27	27
Full Weight(kg) Approx.	1.80	2.00	3.60	5.10	6.30	9.4	13.3	17.3
Discharge Time Approx.(second)	7	7	15	13	16	19	25	23
Temperature Range	-30℃-+60℃	-30℃-+60℃	-30℃-+60℃	-30℃-+60℃	-30℃-+60℃	-30℃-+60℃	-30℃-+60℃	-30℃-+60℃
Fire Rating	8A 34B C	5A 34B C	13A 89B C	13A 113B C	21A 144B C	27A 183B C	34A 233B C	43A 233B C
Mounting Type	Plastic Vehicle	Wire Vehicle	Wire Vehicle	Wall	Wall	Wall	Wall	Wall
Approved to BS EN3	√	√	√	√	√	√	√	√